Vickers Laboratories Ltd - Safety Data Sheet

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 1.3 Revision date: Date printed:

29 September 2025 17 October 2025

Section 1. Identification

Product Identifier 2950

> Product Name BUTANONE tech.

CAS Number 78-93-3

REACH Registration No A registration number is not available as the substance or its uses are exempt, the

annual tonnage does not require a registration or the registration is envisaged for a

later date.

C H COCH =72.11 Molecular Formula

1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Vickers Laboratories Ltd **Supplier**



Grangefield Industrial Estate

Richardshaw Road

Pudsey

West Yorkshire LS28 6QW

UNITED KINGDOM

Phone 44 113 2362811 Fax +44(0)113 2362703 Email safety@viclabs.co.uk Website www.viclabs.co.uk

Emergency Telephone (08:00-16:30)44 113 2362811

(24hr)

(Have this document to hand)

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to regulation (EC) 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720 & UK SI 2020/1567

Flammable liquid, category 2 H225: Highly flammable liquid and vapour. Serious eye damage/irritation, category 2 H319: Causes serious eye irritation. Spec target organ tox - single, category 3 H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to regulation (EC) 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720 & UK SI 2020/1567

Signal word Danger

Hazard Pictograms





Hazard Statements Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary Statements Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective

clothing / eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Store in a well

ventilated place. Keep cool.

Supplemental Hazard Information (EU)

Repeated exposure may cause skin dryness or cracking.

Section 3. Composition

3.1 Substances

Component	CAS No.	EC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Methyl ethyl ketone	78-93-3	201-159-0		>99%	Flam. Liq. 2,Eye Irrit. 2,STOT SE 3 (D)

Section 4. First Aid

4.1 Description of first aid measures

Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL Eyes

Skin Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use. If

discomfort persists OBTAIN MEDICAL ATTENTION.

Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If Inhalation

breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen Ingestion

if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the

recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

Personal protection for first Wear protective gloves / eye protection.

4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

Section 5. Fire Fighting

5.1 Extinguishing media

Extinguishing Media Water spray, foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool.

Unsuitable Media Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards Vapour-air mixtures are explosive.

5.3 Advice for firefighters

Advice for firefighters Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear

protective clothing and breathing apparatus.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate

area immediately. Do not allow general use of area until it is safe to do so. Beware: vapour is heavier than air and

will tend to accumulate at low spots.

6.2 Environmental precautions

Environmental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local

Environmental Health Officer if major spillage occurs.

6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with

copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in

remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

Section 7. Storage & Handling

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage. Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

7.3 Specific end use(s)

See section 1.2.

Section 8. Workplace Exposure & Personal Protection

8.1 Control parameters

Ī	Component	CAS No	Concentration	Workplace Exposure Limits				
				Long Term (8hr TWA)		Short Term 15min period)		
	Methyl ethyl ketone	78-93-3	>99%	200.0 ppm	300.0 mg/m-3	600.0 ppm	899.0 mg/m-3	

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

8.2 Exposure controls

maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.

Hand Protection Use solvent resistant gloves.

Eye Protection Use tightly fitting chemical splash proof glasses or goggles.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance Clear colourless liquid.

Odour Pungent.
pH Not applicable
Boiling Point 79.6°C
Melting Point -85.9°C

Flash Point -3 °C (Closed cup)

Upper Flammable Limit 11% Lower Flammable Limit 1% Auto Ignition 404 °C

Explosive Properties Severe in confined spaces.

Oxidising Properties No.

Vapour Pressure 71.2mmHg @ 20 °C

Relative Density 0.8061 Water Solubility 25%

9.2 Other information

Dynamic Viscosity: 0.41 mPa.s @ 25°C. Kinematic Viscosity: 0.509 mm2/s @ 25°C (Calculated)

Section 10. Stability & Reactivity

10.1 Reactivity No data available.

Stable under normal conditions 10.2 Chemical Stability

10.3 Possibility of hazardous

reactions

No data available.

10.4 Conditions to Avoid Hot surfaces, naked flames or other sources of ignition.

10.5 Incompatible materials Strong oxidising agents.

10.6 Hazardous Decomposition None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

Products

Section 11. Toxicological Information

11.1 Information on toxicological effects

Eyes Both the vapour and liquid may produce conjunctival irritation and corneal damage.

Skin Both the vapour and liquid may be an irritant on brief or occasional exposure. Repeated or prolonged contact may

defat the skin producing irritation and dermatitis.

LD50 Skin 13000mg/kg Rabbit

Ingestion Low order of acute toxicity. Ingestion of large amounts will produce gastrointestinal irritation. and central

nervous system depression, leading to unconsciousness. Aspiration during swallowing or vomiting may injure

lungs.

LD50 Oral 3400mg/kg Rat

Inhalation Exposure to vapour concentrations above the occupational exposure limits will produce irritation of the eyes and

respiratory tract. High concentrations of vapour may produce central nervous system depression and

unconsciousness.

LD50 Inhalation Not available TCLo Not available

Carcinogenicity Not considered to be a carcinogen. Mutagenicity Not considered to be a mutagen.

Reproductive Effects Some evidence for foetoxicity and tetragenecity has been observed in experimental animals

Other Information Odour is noticeable at 25ppm and intensely irritating at 350ppm.

Section 12. Ecological

Bio-oxidation as a % of Theoretical O2 Demand (ThOD) - ThOD 2.44 gm/gm: Fresh water 5 days 76%, 20 days 89%: Salt water 5 days 32%, 20 days 69%. Unlikely to bio-accumulate. Material is practically non-toxic to fish 12.1 Toxicity

on an acute basis (LC50 > 100mg/l.

LC50 Algal Not available LC50 Crustacea Not available LC50 Fish > 100 mg/l

12.2 Persistence and No data available.

degradability

12.3 Bioaccumulative potential No data available. Mobility in soil No data available.

12.5 Results of PBT & vPvB Assessment not required.

assessment

Section 13. Disposal Considerations

13.1 Waste treatment methods

Disposal Methods Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of

into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

Section 14. Transport Information

14.1 UN Number 1193

14.2 Proper Shipping Name Methyl ethyl ketone

14.3 Transport classes

UN classification 3
Subsidiary hazard(s) None
Transport category 2
ADR Hazard ID 33
Tunnel Restriction Code D/E

14.4 Packing Group II

14.5 Environment hazards See section 12.

14.6 Special precautions for No special precautions required.

user

14.7 Transport in bulk Not transported in bulk.

Section 15. Regulatory Information

15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE) as amended by GB-CLP Regulation, UK SI 2019/720 & UK SI 2020/1567

Classification Flammable liquid, category 2; Serious eye damage/irritation, category 2; Spec target organ tox - single, category 3

Signal word Danger

Hazard Pictograms





Hazard Statements H225, H319, H336

Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary Statements P210, P280, P305+P351+P338, P337+P313, P303+P361+P353, P403+P235

Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective clothing / eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Store in a well

ventilated place. Keep cool.

Supplemental Hazard Information (EU)

EUH066

Repeated exposure may cause skin dryness or cracking.

15.2 Chemical safety assessment

Assessment not required.



Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.3 (Supercedes revision 1.2)

Revision date: 29 September 2025

Reviewed by chemist: 29 September 2025

Printed date: 17 October 2025

Copyright: 2025 Vickers Laboratories Ltd